Proposed Claim Amendments Application No. 10/762,209 Attorney Docket No. CHAES7.003AUS For the purpose of Telephonic Interview Only

- 1. (Amended) A mobile phone, comprising: hinge device for coupling
 - a first unit; rotatable about a first rotation axis and
- a second unit, at least one of the first and second units comprising a display, at least one of the first and second units comprising at least one information input device; rotatable about a second rotation axis parallel with the first rotation axis in an apparatus having the first and second units, comprising:
- a hinge device interconnecting the first and second units such that the first and second unit can rotate relative to the hinge device, the hinge device comprising:
 - a housing;
 - a first rotating member adapted to be coupled to the first unit and rotatable about athe first rotation axis with respect to the housing;
 - a second rotating member adapted to be coupled to the second unit and rotatable about athe second rotation axis with respect to the housing;
 - a first linearly moving member cooperating with the first rotating member and linearly movable with respect to the housing;
 - a second linearly moving member cooperating with the second rotating member and linearly movable with respect to the housing;
 - a first resilient member urging the first linearly moving member against the first rotating member; and
 - a second resilient member urging the second linearly moving member against the second rotating member.
- 23. (New) A mobile phone, comprising:
 - a first unit;
- a second unit, at least one of the first and second units comprising a display, at least one of the first and second units comprising at least one information input device;

a hinge device interconnecting the first and second units such that the first and second unit can rotate relative to the hinge device, the hinge device comprising:

- a housing;
- a first rotating member coupled to the first unit and rotatable about a first rotation axis with respect to the housing;
- a second rotating member coupled to the second unit and rotatable about a second rotation axis with respect to the housing;
- a first linearly moving member cooperating with the first rotating member and linearly movable with respect to the housing;
- a second linearly moving member cooperating with the second rotating member and linearly movable with respect to the housing;
- a first resilient member urging the first linearly moving member against the first rotating member; and
- a second resilient member urging the second linearly moving member against the second rotating member.

1673861_1 041905